


# Vehicle PC

# V80T

- Equipped with high-performance ARM octa-core processor and Android 12 OS, up to 4GB+64GB capacity.
- 8-inch screen with 700-Nits high definition display, multiple-point touch panel and customized keys, ensuring outdoor worker visibility.
- 4G LTE, dual-band Wi-Fi and Bluetooth 5.2 connectivity. Multi-satellite systems of GPS/Glonass/Beidou, with available vehicle mushroom antenna for real-time tracking to your vehicle and asset management.
- With aviation plug charging interface, switchable for cigarette lighter interface or  $\Phi$ 4.0 power port, and the external 9V-36V DC wide voltage module is optional.
- Supports the battery-free mode, another optional 3.7V/2000mAh capacity battery.
- Available multiple navigation plug interfaces, and also supports USB/DB9/LAN/CAN and other interface extensions.
- Two bracket mounting methods, VESA and RAM are suitable for almost any vehicle-mounted workplaces.
- IP65 dustproof and waterproof, morphed to endure outdoor applications prone with shock, vibration and extreme temperature.



ARM octa-core processor



Android 12 Operating System



8-inch screen



700cd/cm2




Dual frequency Wi-Fi



GPS/GLONASS/Beidou



Stable power supply



Rich interface extensions



VESA/RAM



IP65



# Vehicle PC V80T

## Specifications




 **CPU**  
MediaTek Helio G99


 **Operating System**  
Android 12

 **Memory**  
RAM: 4GB LPDDR4X  
ROM: 64GB UFS


 **Display**  
Type: LCD  
Size: 8 inch 16:10  
Resolution: 800\*1280 IPS  
Brightness: 700cd/ m<sup>2</sup>

 **Touch Panel**  
5 points Capacitive  
Tempered Glass  
Hardness 6H

 **Dimension/Weight**  
218.1\*154.5\*23.0mm  
620g  
VESA 75 / RAM

 **Buttons**  
Power \*1  
Volume Adjustment Key (+) \*1 (F1 Key)  
Volume Adjustment Key (-) \*1 (F2 Key)  
Customizable \*1 (F3 Key)  
Customizable \*1 (F4 Key)

 **Speaker**  
1.5W \*1, Single horn  
(Maximum 2W)

 **Battery**  
Optional,  
Built in polymer lithiumion battery  
2000mAh/3.7V


 **WIFI**  
WIFI 802.11 (a/b/g/n/ac)  
Dual frequency 2.4G+5.0G (5.1G+5.8G)

 **Bluetooth**  
BT 5.2


 **WAN**  
4G

 **GPS**  
GPS/GLONASS/Beidou

 **NFC**  
Optional

 **I/O Interface**  
Micro-SIM \*1  
USB-A 2.0 \*1  
DC input (Input: 11~24V)  
External SMA Wifi Antenna \*1  
External SMA GPS Antenna \*1  
Default: 100M Ethernet (RJ45)  
RS232 \* 2  
USB 2.0 \* 2  
M12 cables included:  
1 \* M12 to Female RJ45  
1 \* M12 to 2 \* RS-232  
1 \* M12 to 2 \* USB 2.0 female  
1 \* M12 to DC input adapter  
  
Optional: RS232 \*1+RS232/RS485 \*1  
USB 2.0 \*2+CAN/CVBS \*1

 **Certification**  
IP65

 **Rugged Features**  
Working temperature: -20 ° C to 60 ° C  
Storage temperature: -30 ° C to 70 ° C  
±8kV contact discharge,  
±15kV air discharge  
Humidity: 95% Non-Condensing

 **Adapter**  
19V 3.42A Cigarette Lighter Adapter  
19V 3.42A DC φ5.5 power adapter (Default)

\* The technical specifications of this product are subject to change without prior notice

