


Vehicle PC

V10T

- Equipped with ARM octa-core processor and Android 12 operating system, up to 4GB+64GB high-speed capacity.
- 10.1-inch screen with 700-Nits high brightness display, multiple-point touch panel and customized keys , ensuring outdoor worker visibility.
- 4G LTE, dual-band Wi-Fi and Bluetooth 5.2 connectivity. Multi-satellite systems of GPS/Glonass/Beidou, with available vehicle mushroom antenna for real-time tracking to your vehicle and asset management.
- With aviation plug charging interface, switchable for cigarette lighter interface or Φ 4.0 power port, and the external 9V-36V DC wide voltage module is optional.
- Supports the battery-free mode, another optional 3.7V/2000mAh capacity battery.
- Available multiple navigation plug interfaces, and also supports USB/DB9/LAN/CAN and other interface extensions.
- Two bracket mounting methods, VESA and RAM are suitable for almost any vehicle-mounted workplaces.
- IP65 dustproof and waterproof, morphed to endure outdoor applications prone with shock, vibration and extreme temperature.



ARM octa-core processor



Android 12 Operating System



10.1-inch screen



700cd/cm2




Dual frequency Wi-Fi



GPS/GLONASS/Beidou



Stable power supply



Rich interface extensions



VESA/RAM



IP65

Vehicle PC V10T

Specifications



 **CPU**
MediaTek Helio G99

 **Operating System**
Android 12

 **Memory**
RAM: 4GB LPDDR4X
ROM: 64GB UFS

 **Display**
Type: HD
Size: 10.1 inch 16:10
Resolution: 800*1280 IPS
Brightness: 700cd/㎡

 **Touch Panel**
5 points Capacitive
Tempered Glass
Hardness 6H

 **Dimension/Weight**
264.5*184.1*23.0mm
834g
VESA 75 / RAM)

 **Buttons**
Power *1
Volume Adjustment Key (+) *1 (F1 Key)
Volume Adjustment Key (-) *1 (F2 Key)
Customizable *1 (F3 Key)
Customizable *1 (F4 Key)

 **Speaker**
1.5W *1, Single horn
(Maximum 2W)

 **Battery**
Optional,
Built in polymer lithiumion battery
2000mAh/3.7V

 **WIFI**
WIFI 802.11 (a/b/g/n/ac)
Dual frequency 2.4G+5.0G (5.1G+5.8G)

 **Bluetooth**
BT 5.2

 **WAN**
4G

 **GPS**
GPS/GLONASS/Beidou

 **NFC**
Optional

 **I/O Interface**
Micro-SIM *1
USB-A 2.0 *1
DC input (Input: 11~24V)
External SMA Wifi Antenna *1
External SMA GPS Antenna *1
Default: 100M Ethernet (RJ45)
RS232 * 2
USB 2.0 * 2
M12 cables included:
1 * M12 to Female RJ45
1 * M12 to 2 * RS-232
1 * M12 to 2 * USB 2.0 female
1 * M12 to DC input adapter

 **Certification**
IP65

 **Rugged Features**
Working temperature: -20 ° C to 60 ° C
Storage temperature: -30 ° C to 70 ° C
±8kV contact discharge,
±15kV air discharge
Humidity: 95% Non-Condensing

 **Adapter**
19V 3.42A Cigarette Lighter Adapter
19V 3.42A DC φ5.5 power adapter (Default)

* The technical specifications of this product are subject to change without prior notice